

## SPECIFICATION

Specifications	SRX-M1000 Series		
	SRX-M1004	SRX-M1008	SRX-M1016
Compression	MPEG 4		
Operating System	Embedded Linux		
Video Input / Loop Out	4/4	8/8	16/16
Video Output	1 Monitor, 1 S-Video, 1 VGA(Optional), 1 Spot		
Audio In/ Out	4/1	8/1	8/1
Live Display Resolution	NTSC 720*480, PAL 720*576		
Recording Rate	NTSC 30fps(720*480) 60 fps( 720*240), 120fps (360*240) PAL 25fps(720*576) 50 fps (720*288), 120fps (360*288)		
Alarm In/Relay Out	4/2	8/2	16/2
External Recording Devices	Disk Raid, HDD, CD-RW, DVD-RW(- type), Flash Memory Stick		
Communication Port	USB2.0, RS-232, RS-422, Ethernet		
Storage Media	Up to 3 INTERNAL HDDs +CD-RW/DVD-RW		
Network Interface	Ethernet(RJ-45 10/100 base-Tx), External Modem via RS-232C port		
Remote Client Software/Triplex	Central Management Software		
Software Upgrade	Upgrade via USB Flash Memory Stick		

General	
Power	100 or 230VAC Selectable(50/60Hz)
Power Consumption	40W
Dimension / Weight	360(W) x 340(D) x 100(H) / 6 Kg

- Specification may change at any given time without notice.