

SRX S2000 Series SPECIFICATION

Specifications		4CH	8CH	16CH
Video Input/ Loop Out		4/0	8/0	16 /0
Video Output		Monitor, VGA, SPOT-OUT		
Compression		MPEG 4		
Live Display Resolution		NTSC 720*480, PAL 720*576		
Alarm In/Out(Relay)		4/1	8/2	162
Operating System		EMBEDDED LINUX		
System Control		Key buttons, IR Remote, Remote Client, Keypad		
Live Display Speed		4/8/16 CH Real Time		
Maximum	NTSC	30 fps 720*480 ,60 fps 720*240, 120 fps 360*240		
Recording Speed	PAL	25 fps 720*576 ,50 fps 720*288, 100 fps 360*288		
Audio Record		1 IN, 1 Out	4 IN, 1 out	
Features				
Display		Brightness, Contrast, Color Adjustments Per Channel		
Camera Title		12 Characters per Channel		
Recording Mode		Manual, Schedule, Alarm, Motion		
Recording Method		5 Levels of Compression Rate / Record Frame Rate Adjustment		
Recording Adjustments		Pre-Alarm: 3 sec/ Post-Alarm: 10 sec. ~300 sec.		
Motion Detection Per Channel		4*4 Grids (SET)/ 28 x 24 (CMS)/ 20 Sensitivity Levels		
Search Mode		Date & Time, Camera , Alarm / Motion		
Playback Modes		Forward & Reverse: Pause, Frame by Frame, Normal Speed, 2X, 4X, 8X, 16X		
Multi-tasking		Simultaneous Live Display/ Playback, Record or Back-up, Remote Transmission		
Watchdog		Power Failure Recovery: Auto Reboot w/ Maintaining Previous Record Settings		
Watermark		Provided		
Back Up		Internal CD/DVD , USB Flash Memory Stick		
Interface		RS422, Ethernet(10/100 Base-T), USB 1.1		
HDD		1 INTERNAL HDDS + CD RW , DVD RW		
Network		LAN, WAN, Internet,		
Remote Client Software/Triplex		Multi-Site Client Software (CMS), IE		
IR Remote		Control Upto 99 DVRs		
General				
Power		DC 12V		
Operation Temperature		0 ~40		
Dimension / Weight		350(W)*180(D)*82(H)/3.5Kg		